

COMPONENTS OF A SUBSEA DIAMOND WIRE SAW

TENSIONER WHEEL

Ø 10.5MM DIAMOND WIRE ROPE

WIRE DRIVE ASSEMBLY

4 lifting points on each side allow vertical and horizontal lifting.

FEED SCREW

ROTATING LIFT POINTS

4 lifting points on each side allow vertical and horizontal lifting.

IDLER WHEEL

LINEAR GUIDE RAIL



HYDRAULICALLY OPERATED CLAMP ARM

FIXED JAW PLATES


TENSIONER HAND WHEEL

SIZES OF MIRAGE DIAMOND WIRE SAWS

PRODUCT CODE	CUTTING CAPACITY DIAMETER
MDWS620	6 - 20" (152-508mm)
MDWS1638	16 - 38" (406-965mm)
MDWS3660	36 - 60" (914-1524mm)
MDWS6084	60 - 84" (1422-2032mm)

ACCESSORIES

- Top side hydraulic control panel
- Hydraulic power pack
- Flotation
- Hose kits & hydraulic reel
- Hot stab
- Replacement diamond wire ropes
- DNV rated deployment baskets



HYDRAULIC HOSE CONNECTION PANEL
3 CIRCUITS:
CLAMP, FEED AND CUT.

Click below to watch demonstration video on YouTube



FEED UNIT ASSEMBLY

For full details of portable machines for on-site machining projects visit the website www.miragemachines.com

MIRAGE
PORTABLE PERFORMANCE