


COMPONENTS OF A PORTABLE DRILLING MACHINE

Mirage HT50 Portable Drilling Machine: For drilling up to 5" Diameter and with standard stroke of 16"

HYDRAULIC DRIVE MOTOR

- 3.7kw (5 Hp)
- 5 - 60 Rpm as standard. Other motors can be added.
- The HT50 is also available with an air motor



HYDRAULIC FEED MOTOR

Viewed from the side

FEED HANDWHEEL

- Push to engage auto-feed
- Variable auto-feed: 0 - 32mm / min
- Manual feed: 2.5mm / rev

HYDRAULIC HOSE CONNECTORS

LINEAR SLIDES

LINEAR GUIDE BLOCKS

ISO 50 SPINDLE

LIFTING POINT

12.5mm MOUNTING HOLES



Chain clamp mounting option



Switch magnet mounting option

HT50 SPECIFICATION

- Standard stroke: 16" (405mm)
- 31.5" (800mm) stroke available as an option
- Max drill diameter: 5" (125mm)
- RPM: 5 - 60 (with standard motor)

TOOLING OPTIONS INCLUDE:



ISO50 Standard Spindle Tooling



Morse Taper Sleeves



Spade Drills



Sara Drills



Hollow Cutters



Boring Heads

For full details of portable machines for on-site machining projects visit www.miragemachines.com

MIRAGE
PORTABLE PERFORMANCE